

Conductor Platform Datasheet

Conductor Platform	
Ethernet Ports	6 x GbE on RJ-45 ports, auto MDI/MDIX 2 x GbE on SFP sockets
Front Expansion Bays	1 bay for Expansion Module
Rear Expansion Bays	1 x PCIe x8
Controls	1 Multi-Purpose Button 4 Push-buttons on Front Panel Control & Display Unit
Displays	1 Power LED 1 Status LED 1 2-line x 20-character LCD on front panel
Power Input	100-240VAC @ 50-60Hz
Power consumption	360W Max
Storage Temp range	-20° to 70° C (-4° to 158° F)
Operating Temp range	-0° to 40° C (32° to 104° F)
Operating humidity	5% to 90% non-condensing
Enclosure	Rack mount, 1U
Dimensions	438mm W x 321mm D x 44mm H (17.24" W x 12.7" D x 1.74" H)
Weight	6 kg (13.3.lbs.)
Regulatory Approvals	
EMI	FCC Part 15, CISPR (EN55022) class A IC ICES-003
EMS	EN61000-4-2 (ESD), EN61000-4-3 (RS), EN61000-4-4 (EFT), EN61000-4-5 (Surge), EN61000-4-6 (CS), EN61000-4-8, EN61000-4-11
Safety	UL 60950-1, CSA-C22.2 No. 60950-1
Hazardous Substances	RoHS compliant